



AC EV CHARGER

Function Features

Interactive	APP、RFID、OCPP1.6
Intelligent Protection	Over/Under voltage protection, Over current protection, Short-circuit protection, Grounding protection, Over temperature protection, Leakage protection (A+DC6)
Communication	WIFI / 4G
Compliance	IEC 62196-1-2014、IEC 62196-2-2016、IEC 61851-1-2017 IEC 61851-2-2011、IEC 62752-2016、IEC 62893-1-2017 IEC 62893-2-2017、IEC 62893-3-2017、EN 50620

Function Features

Input Voltage	230V ± 20%
Frequency	45Hz ~ 65Hz
Rated Power	7kW / 11kW / 22kW
Output Voltage	230V ± 20%
Output Current	32A
Standby Power	< 5W
Operation Temperature	-30°C ~ +55°C
Relative Humidity	5% ~ 95%
Operation Altitude	≤ 2000m
Protection Rating	IP55
Dimensions	L*W*H : 385mm*265mm*130mm
Package Dimensions	carton packing, L*W*H : 618mm*344mm*259mm
Weight	≤ 8kg (without ground or wall mounted stand)
Cable Length	6m

READY TO UPGRADE?

DROP US A LINE

 info@powerbay.com.au

 1300 000 000

POWER BAY PTY LTD

90 Southlink Street, Parkinson,
Queensland 4115, Australia

5/41 Rose Street, Richmond,
Victoria 3121, Australia